

ICR300H2 is the higher resolution version of the popular ICR300.

ICR-300H2 is a vari-focal weather proof day/night vandal-proof dome camera. It has a 3.5-8.0mm vari-focal lens and utilizes a 1/3 Sony CCD sensor with 540TV lines. The external zoom and focus adjustments make mounting the ICR-300H2 easy regardless of its position. The camera is fully weatherproof (IP66) which makes it suitable for use both indoor and outdoor.



### Main Features:

- 1/3" SONY Super HAD CCD
- 540 TV Lines
- 3.5mm-8mm Vari-Focal Lens
- 1 Lux color; 0 Lux (IR on)
- Vandal Proof
- IP66 Weatherproof
- Flat front glass design
- Up to 60 Feet IR Coverage

### Specifications:

- Image Sensor: 1/3" SONY Super HAD CCD
- Resolution: 540 TV Lines
- Effective Pixel: 297K
- Minimum Illumination: 1 Lux Color; 0 Lux (IR on)
- S/N Ratio: > 50dB
- Signal Format: NTSC / PAL
- Lens: 3.5mm-8mm Vari-Focal
- Gain Control: AUTO
- Auto Shutter (AES): NTSC/EIA: 1/50~ 1/12,000 sec.; PAL/CCIR: 1/50 ~ 1/100,000 sec.
- Gamma Correction: 0.45
- White Balance: Auto
- Infrared LED Range: Up to 60 feet
- Video Output: BNC 1.0Vp-p 75 Ohm
- Power Supply: 12V DC
- Power Consumption: 350mA
- Working Temperature: -0°C ~ +50°C ( 32°F ~ 122°F)
- Working Humidity: 10% - 90%
- Barometric Pressure: 86kpa - 106kpa