

An economic box camera provides sharp clear image and day/night shutter for true clear night vision. It has a wide range applications: home, stores, offices, warehouses, banks. Fitted into one of ICR's weather proof enclosures, it can be installed outdoor.



### Main Features:

- SONY 1/4" High Resolution SONY CCD
- 420 TV Lines
- 0.1 Lux Minimum Illumination
- Day/Night Shutter
- Video/DC Drive

### Specifications:

- Video Sensor: SONY 1/4" High Resolution DSP CCD
- Resolution: 420 TV Lines
- Picture Elements: 512(H) x 492(V) NTSC/EIA; 512(H) x 582(V) PAL/CCIR
- Horiz. Sync. Frequency: NTSC/EIA: 15,734KHz, PAL/CCIR: 15,625KHz
- Vertical Frequency: NTSC/EIA: 60Hz, PAL/CCIR: 50Hz
- Clock Frequency: NTSC/EIA: 19.0699MHz, PAL/CCIR: 18.9375MHz
- Minimum Illumination: 0.8 Lux / F2.0
- Day and Night Shutter: Mechanical shutter to filter out color interference during night
- Scanning System: Interlace 2:1
- S/N Ratio: > 48dB (AGC Off)
- IRIS Control: Video/DC IRIS
- White Balance: Auto
- Gamma Correction: 0.45
- Electronic Shutter Speed: 1/60 to 1/12,000 sec
- Lens: C/CS Lens
- Video Output: 1Vp-p, 75 Ohm
- Power Supply: 12 VDC (+/- 0.5V)
- Power Consumption: 400mA
- Working Temperature: -10°C to +55°C (14°F to 130° F)
- Demension: 5.20"(W) x 2.44"(H) x 1.85"(D) without Lens
- Weight: 550g (1.2lb)