

One of ICR's most popular cameras. This mini dome camera's small size and low profile allow it to virtually go undetected in many installations.

It comes with a 3.6mm lens that can easily be changed to any size all the way up to 12mm. It has a SONY 1/3 CCD sensor as well as a bi-rotating mount which makes focusing a snap.

**Main Features:**

- 1/3" SONY CCD
- 460 TV Lines
- 2.0 Lux
- > 50dB S/N Ratio
- 3.6mm Fix Lens

Specifications:

- Image Sensor: 1.3" SONY Sensor CCD
- Resolution: 460 TV Lines
- Effective Pixel: 297K
- Minimum Illumination: 2.0 Lux
- S/N Ratio: > 50dB
- Signal Format: NTSC / PAL
- Lens: 3.6mm Fixed (optional 4mm, 6mm, 8mm, 12mm)
- Gain Control: Auto
- Auto Shutter (AES): NTSC/EIA: 1/60 ~ 1/20,000 sec.; PAL/CCIR: 1/50 ~ 1/100,000 sec.
- Gamma Correction: 0.45
- White Balance: Auto
- Power Supply: 12V DC
- Working Temperature: -10°C ~ +50°C (14°F ~ 122°F)
- Working Humidity: 10% - 90%
- Barometric Pressure: 86kpa - 106kpa